

WHAT IS CLAIMED IS:

1. A fixture for fixing camera and the likes capable of adjusting the pitching angle of the camera comprising:

a coupling device capable of coupling to stripe-shape objects;

5 an universal joint having a first end fixed to the coupling device and a second end formed with head portion;

a platform having a coupling portion, in which a cavity formed for receiving part of head of the universal joint, an engaging device inserted through the platform for fixing camera or the likes;

10 a fixing member provided with a cavity and to be fixed to the coupling portion of the platform, whereby the head of the universal joint can be received between the cavity of the platform and that of the fixing member, so as to enable the platform to revolve round the universal joint;

a locking assembly disposed between the coupling portion of the platform and the fixing member, whereby to fix the platform to the universal joint after the locking assembly is locked.

2. The fixture for fixing camera and the likes capable of adjusting the pitching angle of the camera as claimed in claim 1, wherein the coupling device includes a first and a second coupling member, both of which are provided with an curved gap respectively for receiving strip-shape object therebetween.

3. The fixture for fixing camera and the likes capable of adjusting the pitching angle of the camera as claimed in claim 1, wherein

the head of the universal joint is spherical formed, the cavity of the platform and that of the fixing member are semi-sphere shaped.

4. The fixture for fixing camera and the likes capable of adjusting the pitching angle of the camera as claimed in claim 1, wherein
5 the engaging device includes an engaging rod, a C-shape retainer ring and a knob, the engaging rod rotatably inserts through the platform, which has an end fixed by a C-shape retainer ring and another end fixed by the knob.

5. The fixture for fixing camera and the likes capable of
10 adjusting the pitching angle of the camera as claimed in claim 1, wherein the locking assembly includes a locking rod and a foldable rod, a first end of the locking rod is disposed between the coupling portion of the platform and the fixing member, a second end of the same is defined with a notch for engaging with the foldable rod, such that the foldable rod can
15 be folded along the notch.

6. The fixture for fixing camera and the likes capable of adjusting the pitching angle of the camera as claimed in claim 5, wherein the foldable rod of the locking assembly can be covered by a sleeve.